

Cedar Shingle Application Instructions

These application instructions are to be used as a guide and are not meant to supersede local building code requirements. Check with the local authority having jurisdiction for special application requirements in your area.

Spacing

Spacing between shingles shall be 1/4 inches to 3/8 inches. Shingle sidelap shall be minimum 1 1/2 inches staggering between joints in adjacent courses and not more than 10% of shingles shall be in direct alignment in alternate courses.

Fasteners

Shingles shall be fastened with two corrosion resistant fasteners placed approximately 1 1/2 inches above the exposure line and 3/4 inches from the edge of the shingle. Fasteners such as Hot dipped galvanized, aluminum or (type 304 or 316 stainless steel) shall be used. If Shingles are treated contact the treatment company for recommended fasteners. In all cases, fasteners shall comply with local building code requirements. Fasteners shall be long enough to penetrate at least 3/4 inches or all the way through the sheathing. Fasteners shall be driven flush with the face of the shingle but should not be over driven past the face of the shingle.

Exposure

Maximum exposure for Cedar Shingles shall be in accordance with the chart below:

	4:12 Slope & Steeper			3:12 to 4:12 Slope		
	No.1 BLUE LABEL	No.2 RED LABEL	No.3 BLACK LABEL	No.1 BLUE LABEL	No.2 RED LABEL	No.3 BLACK LABEL
16 INCH FIVE X	5" 125 mm	4" 100 mm	3 1/2" 90 mm	3 3/4" 95 mm	3 1/2" 90 mm	3" 75 mm
18 INCH PERFECTION	5 1/2" 140 mm	4 1/2" 115 mm	4" 100 mm	4 1/4" 105 mm	4" 100 mm	3 1/2" 90 mm
24 INCH ROYALS	7 1/2" 190 mm	6 1/2" 165 mm	5 1/2" 140 mm	5 3/4" 145 mm	5 1/2" 140 mm	5" 125 mm

The **QAI GOLD STANDARD LABEL** is available to all QAI certified shake and shingle mills who meet the QAI GOLD STANDARD grading and quality control requirements. These requirements exceed all published grading rules for cedar shakes and shingles. The **QAI GOLD STANDARD Label** is identified by a gold band at the top and bottom of the label and is issued to shake and shingle mills that consistently produce a product complying with this standard.

For more information on the **QAI GOLD STANDARD LABEL**, or for detailed application instructions go to the QAI web site at www.qai.org.

RED LABEL

Certification Number

1327

050141

Yellow Cedar Shingles

No. 2 GRADE

COMPLIES WITH ALL GRADING RULES
FOR NUMBER TWO SINGLES

TEAL CEDAR
PRODUCTS
TEAL GRADE
www.tealcedar.com

Printed In Canada

Made In Canada

17897 Trigg Road
Surrey, B.C. V4N 4M8
Phone: (604) 587-8700
Fax: (604) 581-4104
Toll Free: 1-888-995-8325



Inspected by:



Quality Audited by
QUALITY AUDITING INSTITUTE
ICC ES AA-635

CONFORMS WITH
CSSB-97
CSA 0118.1-97 & UBC 15-4

ICC ES EVALUATION REPORT

ESR-2965

PERFECTION

18" x 5 / 2 1/4" (457 mm X 5 / 57.0 mm)

COVERAGE CHART	
81.5 sq. ft. (7.50 m ²)	
BUNDLES	EXPOSURE
4	4 1/2" (114.0 mm)

RED LABEL

PACKING